



Velvet 101606-0041

Velvet is not just another velvet fabric. Apart from being soft, luxurious and elegant, it is very densely woven and short piled which ensures an even surface. The fabric has a beautiful drape, is easy to maintain and works in various environments for both curtain- and upholstery applications. Technically Velvet has very good abrasion value of 50 000 martindale and excellent sound absorbing properties with an alfa value of 0.65. The colour palette has a warm and natural feel with a good balance between light and dark, cold and warm, soft and muted tones.

We thought you'd like...

- the dense fabric ensures excellent sound absorption and abrasion resistance
- the soft surface and heavy drape
- the muted, natural palette, part of the colour co-ordinated Texture Concept



0008




0086




0053




0061




0016




0055



0056



0065




0029




0025




0064



0036



0041



0059



The finely curated Texture Concept celebrates the diversity of woven textiles. The concept provides endless possibilities of combining exquisite textures with different expressions; from delicate, sheer mesh and coarse mélanges to smooth velvet and dense dim-outs, for any room.

The timeless textures, which all drape beautifully, are arranged into colour families making it easy to find the right shade and light filtering property for your project.

The textures (from top):

Harvest

Rye




Earth

Fairy

Moon

Velvet

Product Specification

Design	Almedahls Design Studio
Material	100% Polyester Trevira CS 
Light transmission	Translucent
Width	140 cm, 55,1 inch
Weight	345 g/m ² , 10,18 oz/yd ²
Abrasion resistance SS-EN ISO 12947-2	50 000 Martindale
Pilling SS-EN ISO 12945-2 (scale 1-5)	4 - 5
Light fastness SS-EN ISO 105-B02 (scale 1-8)	5 - 6
Colour fastness to rubbing SS-EN ISO 105-X12 (scale 1-5)	4 - 5 dry 3 - 4 wet
Colour fastness to laundering SS-EN ISO 105-C06 (scale 1-5)	4 - 5
Seam slippage SS-EN ISO 13936-2	Warp 4 mm Weft 4 mm
Shrinkage SS-EN ISO 6330+A1	<1%
Care instructions	 Can be washed in 70°C
Fire resistance standard	IMO Res.A 563 Drapes  IMO Res.A 688 Bedding Component IMO Res.A 652 B1 DIN 4102-1 M1 NFP 92-503-7 Class 1 UNI 9177 BS EN 1021-1 Cigarette test Crib 5 BS 5852 Source 5 BS 7175 Source 0-1-5 Bedspreads
Sound class ISO 354	C
Alfa Value	0,65
Ökotex	Yes
Certificates	SS-EN ISO 14001:2004