

Moor100225


Moor is a classic wool felt with a wonderful warm expression. Made from natural unbleached wool, the fabric has a beautiful, soft melange effect. The colour palette draws inspiration from the heaths of England and has a base of earthy tones with some more colourful additions inspired by wild flowers, autumn leaves and berries. Moor can be co-ordinated beautiful way with our Tartan check upholstery fabric, which is also made from felted wool.

We thought you'd like...

- the warm expression and the earthy colour palette
- the possibility to match with Tartan a contemporary, wool felt, tartan check
- the durable felted wool, inherently flame retardant and stain repellent



0225



0226




0266




0536



0588




0558



0566




0555



0998




0322




0223




0222




0229



0775



0333




0325



0668



0631



0637




0665




0688



0466




0669



0177




0441



0165




0116



0611

Product Specification

Design	Almedahls Design Studio
Material	100% Wool
Width	137 cm, 53,9 inch
Weight	370 g/m ² , 10,9 oz/yd ²
Abrasion resistance SS-EN ISO 12947-2	> 40000 Martindale
Pilling SS-EN ISO 12945-2 (scale 1-5)	3 - 4
Seam slippage SS-EN ISO 13936-2	3 mm
Light fastness SS-EN ISO 105-B02 (scale 1-8)	5
Colour fastness to rubbing SS-EN ISO 105-X12 (scale 1-5)	Dry 4 Wet 4
Colour fastness to dry cleaning SS-EN ISO 105 D01 scale 1-5)	4 - 5
Colour fastness to water spotting SS-EN ISO 105-E16 (scale 1-5)	4 - 5
Colour fastness to perspiration SS-EN ISO 105-E04 (scale 1-5)	4 - 5
Shrinkage SS-EN ISO 3175 1 + 2	Ⓟ <1 %
Care instructions	
Fire resistance standard	BS 5852 Part 1 BS 5852 Part 2, Crib 5 BS 5867 type B FR EN 1021 1 + 2
ÖkoTex	No
Sound class SS-EN ISO 354:2003	C
Alfa Value	0,65
Certificates	SS-EN ISO 14001:2004